



Product Information

D-1001™

Wall and Floor Mastic

Product Description:

DURABOND® D-1001™ Wall and Floor Mastic is a high performance adhesive for the interior installation of all types of ceramic and stone tile (except moisture sensitive marble). DURABOND D-1001 Wall and Floor Mastic is ready to use for a fast, professional installation and provides excellent handling and vertical grab for large bodied tiles and mosaic sheets. DURABOND D-1001 Wall and Floor Mastic exceeds the requirements of ANSI A 136.1 Type I and II.

Suitable Substrates:

- Gypsum Wallboard
- Exterior grade plywood (floors only)
- Gypsum plaster
- Concrete, cement block, masonry walls
- Cement backerboard
- Existing ceramic tile

Directions for Use:

All surfaces must be structurally sound, clean and free of dust, grease, oil, water, curing compounds, and any foreign materials that may inhibit bond. Follow applicable TCA, ANSI, NTCA specifications.

Plywood: Screw or nail loose floorboards. If the subfloor is less than 1" thick, cover it with 1/2" thick exterior grade plywood. Leave a minimum of a 1/4" gap between all sheets or where they abut surrounding walls or fixtures. Fasten plywood with 5d or 6d cement coated screw shank nails.

Concrete: Concrete must be fully cured (at least 28 days after pouring), free of excessive moisture, alkalinity, and hydrostatic pressure. It is the responsibility of the user to determine the condition of all concrete substrates prior to installation.

TYPICAL PHYSICAL PROPERTIES

Open Time	40 - 70 minutes
Adjustability	50 - 90 minutes
Base	Acrylic Co-polymer Latex
Color	White
Weight per Gallon	13 lbs.
Freeze/Thaw	Stable

PERFORMANCE PROPERTIES

		ANSI A136.1, Type I Requirements
Shear Strength, Dry	>550 psi	≥40 psi

Limitations:

- Not recommended for lugback ceramic tile
- Do not use outdoors
- Do not use to mount soap dishes, grab bars or similar fixtures
- Due to limitations of plywood, do not use on plywood in exterior/wet applications or in heavy traffic areas
- Do not use in steam showers or pools, commercial showers, fountains, etc.
- Tile application on plywood floors must dry 48 hours before grouting
- Certain low or non-absorptive tiles may require extended curing times
- Do not use in temperatures below 40°F
- Do not use to install moisture sensitive stone
- Do not use to install translucent white marble

Application:

Apply a thin coat of DURABOND D-1001 Wall and Floor Mastic using the flat side of the trowel to achieve a good mechanical bond to the substrate, then spread the mastic with the recommended size notched trowel for the type of tile being installed.

Apply no more than can be tiled in 45 minutes. Do not set tile after a skin has formed on the mastic. If skinning occurs, re-apply fresh mastic before continuing. Press or twist individual tile or sheets of tile into the combed mastic. Check a tile or sheets of tile occasionally to ensure at least 95% coverage on the back of the tile. Always beat the tile in with a rubber face beating block to ensure maximum contact and bond. Proper installation requires a finished mastic bed thickness of 1/32" after beat-in. Avoid mastic squeeze up between tiles. Do not walk on floors set with DURABOND D-1001 Wall and Floor Mastic for at least 12 hours unless walking boards or plywood sheets are used.

Grouting:

Wait a minimum of 24 hours before using DURABOND grouts. Reference data sheet or packaging for instructions.

Clean Up:

Remove uncured adhesive with soap and warm water. Remove cured adhesive with mineral spirits.

Storage/Shelf Life:

Close container between application cycles and after use. Store at temperatures between 35°F and 100°F. Protect from freezing. Shelf life is one year from manufacturing.

Packaging:

3.5 gallon pails/48 per pallet, (2300 lbs)

4 x 1 gallon case/pallet 2900 lbs.

12 x 1 quarts case/1600 lbs. per pallet

SUGGESTED TROWELS FOR MAXIMUM PERFORMANCE



3/16" x 5/32" V-Notch

- 4-1/4" x 4-1/4" wall tile
- ceramic mosaics
- 4" x 4" & 4" x 8" glazed wall tile

Coverage
50 sq. ft. per gallon



1/4" x 1/4" x 1/4" Square Notch

- Large Bodied Tiles

Coverage
30 sq. ft. per gallon

PLANT LOCATIONS

TEMECULA, CA 92590

CONYERS, GA 30207

TWINSBURG, OH 44087

PAULSBORO, NJ 08066

www.bostikfindley-us.com

September 2001; Supersedes all previously published literature.

LIMITED WARRANTY

All statements, technical information and recommendations set forth herein are based on tests which Bostik Findley believes to be reliable. However, Bostik Findley does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley's order acknowledgement. Bostik Findley warrants that the product conforms with Bostik Findley's written specifications, and is free from defects. BOSTIK FINDLEY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK FINDLEY BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.