

# CERAMASEAL® PRODUCT INFORMATION

## GROUT STAIN

*Changes the color of cement grout or other concrete surfaces*

### PRODUCT USES

CeramaSeal® Grout Stain stains even the darkest grout to a light color. Grout Stain dries to a matte finish which maintains the granular appearance of a ceramic tile grout joint. It provides a glare-free, non-skid, uniform color grout surface that highly resistant to wear, sunlight, water and temperature extremes.

Grout Stain is available in all Hydroment and Durabond Brand grout colors (except Natural). Use Grout Stain to enhance or change the color of cement grouts or other concrete surfaces.

**NOTE: Always test Grout Stain in an inconspicuous area to ensure product satisfaction.**

### Directions For Use:

Read and understand data sheet completely before beginning installation. Always do a test to ensure product satisfaction and/or to become familiar with proper application techniques prior to use.

Stir Grout Stain thoroughly; do not thin or dilute with a solvent or lacquer thinner. When using more than one container, mix together to avoid any color variance. For best results, apply Grout Stain with a narrow paint brush (1/4" to 1/2"). Apply a thin, uniform coat and brush in well. For narrow grout joints (1/8" or less), or when applying to large surface areas, a short-napped roller may be used. Regardless of the application method, if a second coat is necessary for more uniform color, allow thorough drying between coats. Clean off excess Grout Stain on tile using a cloth dampened with mineral spirits.

### DRY TIME

Grout Stain becomes surface dry in approximately 4 hours (time will vary depending on temperature). Surface should not receive heavy traffic for 24 hours, and avoid washing for 48 hours.

### CLEAN UP

Wipe up any spatters of Grout Stain immediately with a solvent-dampened cloth. Clean tools and equipment promptly with a standard hydrocarbon-based solvent or lacquer thinner.

### COVERAGE

Coverage per 16 oz. container:

1/4" to 3/8" joints- about 300 ft<sup>2</sup> of joint surface.

1/2" joints- about 150 ft<sup>2</sup> of joint surface.

### STORAGE/ SHELF LIFE

Store in a clean, dry, cool area. Keep container tightly closed when product is not in use. Shelf life is one year from date of manufacturing.

### PACKAGING

Grout Stain is available in 16 oz. containers. For the name of a distributor nearest you, contact Customer Service at 1-888-592-8558.

### BOSTIK FINDLEY

MIDDLETON, MA 01949

(800) 7-BOSTIK/(800) 726-7845

### TECHNICAL SERVICES

(800) 523-6530

### PLANT LOCATIONS

TEMECULA, CA 92590

TWINSBURG, OH 44087

CONYERS, GA 30207

PAULSBORO, NJ 08066

### LIMITED WARRANTY

All statements, technical information and recommendations set forth herein are based on tests which Bostik Findley believes to be reliable. However, Bostik Findley does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley's order acknowledgement. Bostik Findley warrants that the product conforms with Bostik Findley's written specifications, and is free from defects. BOSTIK FINDLEY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK FINDLEY BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.

