

# CERAMASEAL® PRODUCT INFORMATION

## MAGIC SEAL™

*A premium stain repellent for grout, marble, granite, limestone and stone tiles*

### PRODUCT USES

CeramaSeal® Magic Seal™ protects against the staining of marble, granite and clay ceramic tile, quarry tile, grout and other absorptive stone surfaces. It provides excellent long-term protection from stains caused by food oils and grease, wine, mineral and petroleum oils, cosmetics, graffiti, and water-based stains such as grape juice and alcohol. Magic Seal is an invisible, water-based repellent that will not change the appearance of the treated surface. It contains no solvents, is environmentally friendly and odorless.

Use Magic Seal on kitchen countertops; marble, limestone and granite tabletops and floors; bathrooms; shower stalls; foyers; commercial entrance ways; areas subject to continuous moisture; concrete driveways, garage floors; brick and masonry surfaces, as well as exterior stone clad building facades. Magic Seal is for use in interior or exterior areas.

### APPLICATION

#### Directions For Use:

Read and understand data sheet completely before beginning installation. Always do a test to ensure product satisfaction and/or to become familiar with proper application techniques prior to use.

Surfaces and ambient temperatures must be above 40°F. Apply evenly to surface using a clean, white, absorbent cotton cloth; paint brush; roller or spray applicator. Avoid puddling to obtain maximum coverage. Once dry, wipe off remaining residue with a clean, white cotton cloth. Porous surfaces may require multiple applications for optimum performance.

### DRY TIME

Surfaces are ready to use when dry. For best performance, allow to cure for 4 hours after application.

### CLEAN UP

Clean all tools and equipment with water.

### LIMITATIONS

- Not suitable for use in areas subject to hydrostatic pressure.

### MAINTENANCE

Clean treated surfaces regularly using CeramaSeal Stone Soap™ or CeramaSeal Tile & Stone Cleaner™.

### COVERAGE

Coverage will vary between 300 and 1,000 ft<sup>2</sup> per gallon depending on the porosity of the material to be sealed and method of application.

### STORAGE/ SHELF LIFE

Store at temperatures between 35°F and 120°F. Product is freeze/thaw stable. Shelf life is one year from date of manufacturing.

### PACKAGING

Magic Seal is available in pint (12/case), and quarts (12/case). For the name of a distributor nearest you, contact Customer Service at 1-888-592-8558.



### BOSTIK FINDLEY

MIDDLETON, MA 01949

(800) 7-BOSTIK/(800) 726-7845

### TECHNICAL SERVICES

(800) 523-6530

### PLANT LOCATIONS

TEMECULA, CA 92590

TWINSBURG, OH 44087

CONYERS, GA 30207

PAULSBORO, NJ 08066

### LIMITED WARRANTY

All statements, technical information and recommendations set forth herein are based on tests which Bostik Findley believes to be reliable. However, Bostik Findley does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley's order acknowledgement. Bostik Findley warrants that the product conforms with Bostik Findley's written specifications, and is free from defects. BOSTIK FINDLEY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK FINDLEY BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.

