

CERAMASEAL® PRODUCT INFORMATION

STONE ENHANCER™ *Enhances and highlights natural coloring*

PRODUCT USES

Apply CeramaSeal® Stone Enhancer™ to any non-polished stone to highlight geological features such as veins, mineral deposits and color shades. Apply Stone Enhancer to cement grouts, pre-cast tiles to strengthen color and/or provide a "wet" look. Can be used with:

- Tumbled Marble
- Slate
- Sawn Granite, Marble, Limestone
- Flamed Granite
- Flamed Limestone
- Honed Marble
- Honed Limestone
- Travertine
- Cement Tile Grout

FEATURES AND BENEFITS

- Non Yellowing
- Low Odor
- Interior & Exterior
- Easy application
- Enhances grout color

Directions For Use:

Read and understand data sheet completely before beginning installation. Always do a test to ensure product satisfaction and/or to become familiar with proper application techniques prior to use.

New Installations:

Prior to grouting, seal with CeramaSeal Silox 8™ according to instructions. Take care not to puddle Silox 8 in grout joints. Do not apply 2 coats of Silox 8 prior to the application of Stone Enhancer.

Before grouting, allow the Silox 8 to dry for 12-24 hours.

Allow 24 hours after the grout has set and been completely

cleaned. Seal the grout with Silox 8 according to instructions. Allow 2-4 hours to dry.

Apply Stone Enhancer with a clean cotton towel or lambs wool applicator. Allow the Stone Enhancer to penetrate the surface for 5-10 minutes. Wipe up excess Stone Enhancer with a clean, dry absorptive towel. Multiple applications of Stone Enhancer may be required to achieve desired look.

Existing Installations:

Seal the stone and the grout with Silox 8 according to container instructions.

Apply Stone Enhancer with a clean cotton towel or lambs wool applicator. Allow the Stone Enhancer to penetrate the surface for 5-10 minutes. Wipe up excess Stone Enhancer with a clean dry absorptive towel. Multiple applications of Stone Enhancer may be required to achieve desired look.

To Enhance Grout:

Stone Enhancer is an effective product to enrich the color of cement grouts. Apply directly to grout using a paint brush. Allow Stone Enhancer to penetrate for 5-10 minutes. Wipe away excess with a clean absorbent towel.

DRY TIME

Stone Enhancer usually dries within 2-4 hours depending on the temperature and the porosity of the stone being treated.

CLEAN UP

Clean tools and spills with an absorbent towel dampened with mineral spirits.

LIMITATIONS

- Do not let Stone Enhancer dry or become sticky before removing excess.
- Always perform a "mock-up" to ensure suitability and the number of applications required of Stone Enhancer prior to the installation.

COVERAGE

The amount of Stone Enhancer required will vary a great deal depending on the texture and porosity of the material being treated.

Tumbled Marble, Slate - 200-300 ft²/gallon

Sawn Marble/Granite - 300-500 ft²/gallon

Honed Marble/Granite/Limestone - 500-800 ft²/gallon

STORAGE/ SHELF LIFE

Store in a clean, dry, cool area. Keep container tightly closed when product is not in use. Shelf life is one year from date of manufacture.

PACKAGING

Stone Enhancer is available in pints (12/carton) and quarts (12/carton). For the name of a distributor nearest you, contact Customer Service at 1-888-592-8558.

BOSTIK FINDLEY

MIDDLETON, MA 01949

(800) 7-BOSTIK/(800) 726-7845

TECHNICAL SERVICES

(800) 523-6530

PLANT LOCATIONS

TEMECULA, CA 92590

TWINSBURG, OH 44087

CONYERS, GA 30207

PAULSBORO, NJ 08066

LIMITED WARRANTY

All statements, technical information and recommendations set forth herein are based on tests which Bostik Findley believes to be reliable. However, Bostik Findley does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley's order acknowledgement. Bostik Findley warrants that the product conforms with Bostik Findley's written specifications, and is free from defects. BOSTIK FINDLEY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK FINDLEY BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.

