

CERAMASEAL® PRODUCT INFORMATION

TUB & TILE CAULK

PRODUCT USES

CeramaSeal® Tub & Tile Caulk is an odorless, one-part, self-curing, acrylic latex caulk which provides a flexible seal that bonds to most common household surfaces. Tub and tile caulks are designed to complement Hydroment® & Durabond® grout colors.

APPLICATION

Directions For Use:

Read and understand data sheet completely before beginning installation. Always do a test to ensure product satisfaction and/or to become familiar with proper application techniques prior to use.

Use Ceramaseal Tub & Tile Caulk to seal around bathtubs, shower enclosures, vanities, countertops, basins and many other areas.

NOTE: FOR INTERIOR, RESIDENTIAL OR LIGHT COMMERCIAL USE ONLY

Application: Do not apply where surface or ambient temperatures are below 40°F. Cut cartridge nozzle with a sharp blade to desired size for particular application. The inner foil seal must be punctured with an awl, wire or screwdriver. Insert cartridge into caulking gun. Apply caulking while holding at a 45° angle, gun material into joint. Do not "pump" action of gun before end of joint to avoid excess material in the joint. After installation of caulk, the joint should immediately be tooled with a spatula, spoon or similar item to reduce voids and provide a consistent joint. Allow finished joint to cure 24 hours before subjecting it to water or contact.

Surface Preparation: All surfaces must be clean, dry and free from surface contaminants including previous waxes, coatings and sealants.

LIMITED WARRANTY

All statements, technical information and recommendations set forth herein are based on tests which Bostik Findley believes to be reliable. However, Bostik Findley does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley's order acknowledgement. Bostik Findley warrants that the product conforms with Bostik Findley's written specifications, and is free from defects. BOSTIK FINDLEY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK FINDLEY BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.



DRY TIME

Siloxane 220 typically dries within 2-4 hours depending on local temperature and humidity.

CLEAN UP

Clean all tools with soap and warm water. Remove cured caulk with a sharp blade.

LIMITATIONS

- Not for use in joints subjected to high degrees of movement
- Not for use in areas subject to continuous immersion in water
- Cure for at least 24 hours before exposing to freezing temperatures or intermittent moisture contact
- Not recommended for joints wider than 3/8"
- Do not apply in temperatures below 40°F
- NOT FOR USE IN STEAM ROOMS OR COMMERCIAL KITCHENS & SHOWERS (USE PURE SILICONE CAULK)

STORAGE/ SHELF LIFE

Store in temperatures between 40°F and 100°F. Shelf life is one year from the date of manufacturing.

PACKAGING

CeramaSeal Tub & Tile Caulk is available in 10.1 oz. cartridges (6/case). For the name of a distributor nearest you, contact Customer Service at 1-888-592-8558.

PLANT LOCATIONS

TEMECULA, CA 92590
TWINSBURG, OH 44087

CONYERS, GA 30207
PAULSBORO, NJ 08066