

Mixed Colours and Textures Make Way For Creativity

Crystal Stone mosaics are compositions of stone and glass fragments with different surfaces - rough and smooth, transparent and opaque, becoming a ductile tool in the hands of architects and interior designers. Warm, welcoming colours create an attractive effect of intimacy: a grading choice of shades taken from nature, with its range of tints and the changeable tactile perception of its surfaces.







Matching Solids and Transparency

Crystal Stone mosaics provide an original interpretation of the glass tile body mixed with stone, giving variety to the mosaics surface. Geometrical lines generate the optical impression of motion, in a range of exquisite shades, for sophisticated, contemporary design projects. The well-balanced mix of colours and surfaces increases the materials depth, the simple, versatile patterns communicate an unusual, sophisticated taste.

7









Natural Inspiration

The mosaic acquires the transparency and freshness of water, enclosed in uniform modules that transform walls into iridescent surfaces, welcoming and conversing with the passing light. The finest design is achieved through dynamic surfaces and three-dimensional effects of unexpected beauty. The natural inspiration of the material mediated by modern design and technology, retains all its poetry and is enhanced by fresh faceting effects, giving original visions of living space.

























Shade variations

The color and shade of all tiles vary to some degree. This variance can be from piece to piece and can also occur from production run to production run.

The Ceramic Tile Distributor Association (CTDA), in cooperation with tile manufacturers and distributors, has put together helpful literature entitled the CTDA Color Shade Variation Guide. This guide rates ceramic tile on a four-point scale and ranges from V1 through V4.

Instituting the CTDA's color shade variation guidelines you will reduce customer complaints and sell the unique and individual beauty of each ceramic tile.



V1 Slight Shade Variation

The range of color and/ or finish within the same shade is relatively uniform from tile to tile.

V2 Average Shade Variation

The range of color and/ or finish within the same shade is moderately noticeable from tile to tile.

V3 Heavy Shade Variation
The range of color and/ or finish within the same shade is distinctly different from tile to tile.

V4 Extreme Shade Variation

The range of color and/ or finish within the same shade is extensively random from tile to tile.

SHADE VARIATION AND APPLICATIONS								
V2		Residential	Commercial	Industrial				
	Floor	•						
	Wall	•	•	•				
	Countertop	•						
AVERAGE VARIATION	Pool	•	•	•				

Water, oil, grease, or other fluids create slippery conditions. Floors with exposure to these conditions require extra caution in product selection and proper maintenance.

Care & Maintenance

Crystal Stone is a stain-resistant porcelain tile. Routine maintenance will keep your tile looking new for years to come.

Ragno USA's products are typically easy to install and maintain using the following general guidelines:

- Choose tile from same dye lot and caliber whenever possible
- Select tile alternately from several boxes and rotate when installing
- Follow industry-accepted installation practices as detailed by Tile Council of America "Handbook for Ceramic Tile Installation" or those recommended by the Ceramic Tile Institute of America
- Remove all grout residue promptly after application; neither acid cleaning nor sealing is recommended
- Clean regularly with clear water and/or a neutral (soapless) cleaner, wipe dry to lessen slippery conditions

TECHNICAL SPECIFICATIONS									
DESCRIPTION		RESULT	ASTM#						
Water Absorption		2% - 5%	C373						
PEI Rating		3	C1027						
MOHS (Scratch Resistance)		6	MOHS Scale						
Frost Resistant		Resistant	C1026						
C.O.F. Wet		0.40 ≤ COF < 0.50	C1028						
C.O.F. Dry		0.60 ≤ COF < 0.70	C1028						
Breaking Strength		N/A	C684						
Chemical Resistance	ACID	Excellent	C650						
	BASE	Excellent	C650						

PACKAGING										
	SIZE	THICKNESS	BOX			PALLET				
			PCS	SQ FT	LBS	BOXES	SQ FT	LBS		
Field Tile	12"x12"	5/16"	12	11.63	42.00					







Wall Tile













