

RUSTICA CERAMIC TILE



RUSTICA CERAMIC TILE



13" x 13" RUSTICA IVORY FLOOR TILE
46-008



3" x 8" RUSTICA IVORY BULLNOSE
52-020



8" x 10" RUSTICA IVORY WALL TILE
52-019



13" x 13" RUSTICA ALMOND FLOOR TILE
46-010



3" x 8" RUSTICA ALMOND BULLNOSE
52-024



8" x 10" RUSTICA ALMOND WALL TILE
52-023

RUSTICA CERAMIC TILE



13" x 13" RUSTICA NOCE FLOOR TILE 46-011



3" x 8" RUSTICA NOCE BULLNOSE 52-028



8" x 10" RUSTICA NOCE WALL TILE 52-027



13" x 13" RUSTICA GREEN FLOOR TILE 46-007



13" x 13" RUSTICA MOCA FLOOR TILE 46-012



13" x 13" RUSTICA BLACK FLOOR TILE 46-009

RUSTICA CERAMIC TILE

PACKAGING INFORMATION

DESCRIPTION	ITEM CODE						LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	IVORY	BLACK	ALMOND	NOCE	MOCA	GREEN					
13" x 13" RUSTICA FLOOR TILE	46-008	46-009	46-010	46-011	46-012	46-007	26.98	9	10.76	68	731.68
8" x 10" RUSTICA WALL TILE	52-019	N/A	52-023	52-027	N/A	N/A	12.87	20	10.76	68	989.92
3" x 8" RUSTICA BULLNOSE	52-020	N/A	52-024	52-028	N/A	N/A	12.87	30	N/A	N/A	N/A

GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	13" x 13"
THICKNESS		mm – in	7.8 mm – 5/16"
WATER ABSORPTION	EN ISO 10545-3	(%)	≤ 3
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	3 - 4*
SCRATCH HARDNESS		(Mohs)	6
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 400
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.60
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.80
DCOF (WET)	ANSI B101.3		≥ 0.42
SHADE VARIATION			V2

* Additional abrasion resistance (pei) information.