

SATURNIA PORCELAIN TILE



SATURNIA PORCELAIN TILE



13" x 13" SATURNIA OSSO PORCELAIN TILE
63-374



3" x 8" SATURNIA OSSO BULLNOSE
52-182



8" x 10" SATURNIA OSSO WALL TILE
52-063



13" x 13" SATURNIA WALNUT PORCELAIN TILE
63-375



3" x 8" SATURNIA WALNUT BULLNOSE
52-183



8" x 10" SATURNIA WALNUT WALL TILE
52-067

SATURNIA PORCELAIN TILE



13" x 13" SATURNIA ALBASTRINO PORCELAIN TILE
63-376



3" x 8" SATURNIA ALBASTRINO BULLNOSE
52-184



8" x 10" SATURNIA ALBASTRINO WALL TILE
52-071

PACKAGING INFORMATION

DESCRIPTION	ITEM CODE			LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	OSSO	WALNUT	ALBASTRINO					
13" x 13" SATURNIA POCELAIN TILE	63-374	63-375	63-376	45.21	11	12.91	58	748.90
8" x 10" SATURNIA WALL TILE	52-063	52-067	52-071	27.2	20	10.76	90	968.40
3" x 8" SATURNIA BULLNOSE	52-182	52-183	52-184	19.98	45	N/A	N/A	N/A

GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	13" x 13"
THICKNESS		mm – in	7.7 mm – 5/16"
WATER ABSORPTION	EN ISO 10545-3	(%)	≤ 0.5
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	4
SCRATCH HARDNESS		(Mohs)	6
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 300
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.60
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.60
DCOF (WET)	ANSI B101.3		≥ 0.42
SHADE VARIATION			V2