

VINTAGE WOOD HD PORCELAIN TILE



## VINTAGE WOOD HD PORCELAIN TILE



6" x 24" VINTAGE WOOD DUNE HD PORCELAIN TILE

## VINTAGE WOOD HD PORCELAIN TILE



6" x 36" VINTAGE WOOD DUNE HD PORCELAIN TILE  
62-700



6" x 24" VINTAGE WOOD DUNE HD PORCELAIN TILE  
62-500



6" x 36" VINTAGE WOOD ASH HD PORCELAIN TILE  
62-703



6" x 24" VINTAGE WOOD ASH HD PORCELAIN TILE  
62-503



6" x 36" VINTAGE WOOD SADDLE HD PORCELAIN TILE  
62-701



6" x 24" VINTAGE WOOD SADDLE HD PORCELAIN TILE  
62-501

## VINTAGE WOOD HD PORCELAIN TILE



6" x 36" VINTAGE WOOD SADDLE HD PORCELAIN TILE

## VINTAGE WOOD HD PORCELAIN TILE



6" x 36" VINTAGE WOOD CINNAMON HD PORCELAIN TILE  
62-702



6" x 24" VINTAGE WOOD CINNAMON HD PORCELAIN TILE  
62-502



6" x 36" VINTAGE WOOD CARBON HD PORCELAIN TILE  
62-704



6" x 24" VINTAGE WOOD CARBON HD PORCELAIN TILE  
62-504

## VINTAGE WOOD HD PORCELAIN TILE



6" x 36" VINTAGE WOOD CINNAMON HD PORCELAIN TILE

## VINTAGE WOOD HD PORCELAIN TILE

### PACKAGING INFORMATION

DESCRIPTION	ITEM CODE	LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
6" x 36" VINTAGE WOOD DUNE HD PORCELAIN TILE	62-700	48.21	8	12	39	468
6" x 24" VINTAGE WOOD DUNE HD PORCELAIN TILE	62-500	55.01	14	14	40	560
6" x 36" VINTAGE WOOD ASH HD PORCELAIN TILE	62-703	48.21	8	12	39	468
6" x 24" VINTAGE WOOD ASH HD PORCELAIN TILE	62-503	55.01	14	14	40	560
6" x 36" VINTAGE WOOD SADDLE HD PORCELAIN TILE	62-701	48.21	8	12	39	468
6" x 24" VINTAGE WOOD SADDLE HD PORCELAIN TILE	62-501	55.01	14	14	40	560
6" x 36" VINTAGE WOOD CINNAMON HD PORCELAIN TILE	62-702	48.21	8	12	39	468
6" x 24" VINTAGE WOOD CINNAMON HD PORCELAIN TILE	62-502	55.01	14	14	40	560
6" x 36" VINTAGE WOOD CARBON HD PORCELAIN TILE	62-704	48.21	8	12	39	468
6" x 24" VINTAGE WOOD CARBON HD PORCELAIN TILE	62-504	55.01	14	14	40	560

### GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	6" x 24"	6" x 36"
THICKNESS		mm – in	9 mm – 11/32 in	9 mm – 11/32 in
WATER ABSORPTION	EN ISO 10545-3	( % )	≤ 0.5	≤ 0.5
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	3 – 4	3 – 4
SCRATCH HARDNESS		(Mohs)	8	8
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 350	≥ 350
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Resistant	Class A – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant	Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.70	≥ 0.70
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.70	≥ 0.70
DCOF (WET)	ANSI B101.3		≥ 0.50	≥ 0.50
SHADE VARIATION			V2	V2



6" x 36" VINTAGE WOOD CARBON HD PORCELAIN TILE