

RAGNO  USA

JUST™ COLOR BODY PORCELAIN TILE | MADE IN THE USA



live inspired





live inspired

JUST™

COLOR BODY PORCELAIN TILE | MADE IN THE USA




UH5P Avorio
20"x20"
UH5J Avorio
13"x13"
UH6F Avorio
10"x20"
UH5U Avorio
4"x20"



UH6L Avorio
Mosaic - Square 1"x1"
13"x13"



UH6R Avorio
Mosaic - Brick 1"x3"
13"x13"



UH6W Avorio
Mosaic - Metal Insert
13"x13"




UH5Q Beige
20"x20"
UH5K Beige
13"x13"
UH6G Beige
10"x20"
UH5V Beige
4"x20"



UH6M Beige
Mosaic - Square 1"x1"
13"x13"




UH6S Beige
Mosaic - Brick 1"x3"
13"x13"



UH6X Beige
Mosaic - Metal Insert
13"x13"




UH5R Noce
20"x20"
UH5L Noce
13"x13"
UH6H Noce
10"x20"
UH5W Noce
4"x20"



UH6N Noce
Mosaic - Square 1"x1"
13"x13"




UH6T Noce
Mosaic - Brick 1"x3"
13"x13"



UH6Y Noce
Mosaic - Metal Insert
13"x13"




UH5S Oro
20"x20"
UH5M Oro
13"x13"
UH6J Oro
10"x20"
UH5X Oro
4"x20"



UH6P Oro
Mosaic - Square 1"x1"
13"x13"



UH6U Oro
Mosaic - Brick 1"x3"
13"x13"



UH6Z Oro
Mosaic - Metal Insert
13"x13"



UH5T Blu
20"x20"
UH5N Blu
13"x13"
UH6K Blu
10"x20"
UH5Y Blu
4"x20"



UH6Q Blu
Mosaic - Square 1"x1"
13"x13"



UH6V Blu
Mosaic - Brick 1"x3"
13"x13"



UH6I Blu
Mosaic - Metal Insert
13"x13"



UH62 Avorio Bullnose
UH63 Beige Bullnose
UH64 Noce Bullnose
UH65 Oro Bullnose
UH66 Blu Bullnose
3"x13"

TRIMS



Floor Tile



Wall Tile



Modular Tile



Decorative Tile



Trim Available



Suitable for
Outdoors



Substantial
Variation



Frost Resistant



Abrasion Resistance



0.5 S.C.O.F. (Wet)
(Valid Through 12-31-2013)



0.7 S.C.O.F. (Dry)
(Valid Through 12-31-2013)



21% Minimum
Pre-Consumer
Recycled Content



No VOC



Contributes to
LEED Credits

made in the
USA

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS SCALE
Breaking Strength	≥ 250 lbf.	≥ 405 lbf.	C648
Facial Dimension	+/- 3.0 % from Nominal	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm**	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm**	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
DCOF - Dynamic Coefficient of Friction (We Areas Only) [†]	As Reported	Less than 0.42	DCOF AcuTest SM *
SCOF-Static Coefficient of Friction (Wet)	As Reported	0.50 ≤ SCOF < 0.60	C1028
SCOF-Static Coefficient of Friction (Dry)	As Reported	0.70 ≤ SCOF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

[†]Dynamic Coefficient of Friction (DCOF) - Water, oil, grease or other fluids create slippery conditions. When installing floors in areas with exposure to these conditions, a minimum D.C.O.F. value of 0.42 is required. Additionally, extra caution is required with regards to product selection and proper maintenance. Visit www.tcnatile.com for complete information regarding the DCOF Acutest test method and values.

*DCOF AcuTest is the industry designation for the test procedure contained in ANSI A137.1 Section 9.6, which has been extensively researched, allows for in-situ field measurements, and is in use at tile manufacturing facilities. It was so named to distinguish it from other DCOF measurements using different instruments and/or protocols.

** Whichever is less

